



# FAÇADE CREATIONS



Luminia  
Brochure



## Innovation, not imitation

The Luminia F82 bi-fold door has been designed with style and performance front of mind. It cleverly combines the intimacy of inside spaces with the freedom of outside living, without ever compromising on performance safety or security.

And like all AluK aluminium façade systems, it continues to push the industry forward by delivering unrivalled innovation and installation simplicity.

For starters, it delivers an industry-best 1.3 U-value thermal performance for double glazed units and 0.9 U-value for triple glazed. Larger glazing panels, faster fabrication and installation thanks to fewer parts and profiles. While panel size options of up to 3000mm\* provide complete project flexibility.

As ever, we believe the highest levels of safety and security should be as standard, not an aspiration. It is why the F82 conforms to the latest British Standards and Building Regulations such as Document Q and L including PAS24\*\*.

The F82 bi-fold is available exclusively through our Luminia Select Partner Network to our most valued and trusted customers.



Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors

## Intelligently simple

We have a passion for innovation at AluK. The Luminia F82 bi-fold continues the trend.

To speed up fabrication, we've reduced the number of parts and profiles without compromising on the ease of installation.

It boasts all-new contemporary flush hardware, while the new elegant slimmer symmetrical sightlines of the frame and panels provide larger glazing area than others on the market. Flooding the home with more natural light.



Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors




## Typically **unique**

As the experts for designing and engineering aluminium window, door and bi-fold systems, we're famous for delivering industry firsts. It's why we've pushed ourselves to ensure the Luminia F82 equally leads the way.

Designed and engineered to withstand all that the British weather can throw at it, from exceptional performance for Air, Wind and Water resistance. Our Patent Applied F82 bi-fold door has been designed to ensure the best performance and durability throughout its life.

It has unrivalled thermal performance of 1.3 W/m<sup>2</sup>K with a double glazed unit and 0.9 W/m<sup>2</sup>K with a triple glazed unit. Which help to reduce heating bills, while keeping the warmth in longer.



### LUMINIA F82 ISOTHERM

The thermal improvement design encompasses an improved in-line and uniform thermal break. Heat transfer is optimised throughout the centre of the system resulting in market leading U-value performance.



Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors

## Impossibly effortless

Everything about the Luminia F82 has been developed with homeowner demands and ease of use front of mind.

The system is designed with heavy duty slim stainless steel rollers as standard and also boasts a unique gearbox for smoother operation.

While the all-new, unique flush pop-out T-handle provides ease of operation, removing the need for additional unsightly handles as well as delivering stand out design from the crowd.



### LOW THRESHOLD OPTION

Maximises ease of accessibility  
without compromising thermal efficiency

## Born performer

To ensure total peace of mind, the F82 has been put through its paces to ensure it conforms to all the latest British Standard and Building Regulations for thermal, security and safety including PAS24\*\*

For added security, the Luminia F82 features shootbolts top and bottom of the interlock along with a dedicated bottom bogey guide. For greater stability, there's also the double track threshold.

And for extra safety, magnetic catches that hold the doors in place whilst being operated. As well as an anti-finger trap system, using gaskets, to prevent fingers getting trapped when the doors are closing.




Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors

# Clear choice

We understand every project is different, which is why the Luminia F82 is available with panels up to 3000mm\* and weights of 150Kg. We also offer glazing add-ons and the option for both internal and external glazing.

| PERFORMANCE AND ACCREDITATION                           |                              |
|---|------------------------------|
| *U-value (double glazing)                               | 1.3 W/m <sup>2</sup> K       |
| *U-value (triple glazing)<br>(Ug0.5 W/m <sup>2</sup> K) | 0.9 W/m <sup>2</sup> K       |
| Air tightness (Pa)<br>(standard threshold)              | Class 4 (600pa)**            |
| Water tightness (Pa)<br>(standard threshold)            | Class 9a (600pa)**           |
| Wind load (Pa)  | Class 5 (2000pa)**           |
| Security  | PAS 24**                     |
| DESIGN DETAILS  |                              |
| Max vent weight   | 150kg                        |
| Sightline (Head)  | 97mm                         |
| Sightline (Cill)  | 97mm                         |
| Sightline (Jamb)  | 97mm                         |
| Sightline (Meeting stile)                               | 122mm                        |
| Maximum leaf height                                     | 2500mm std > 3000mm          |
| Maximum leaf width                                      | 1200mm                       |
| SYSTEM FEATURES   |                              |
| Frame depth   | 82mm                         |
| Dual colour option                                      | ✓                            |
| Multi-point locking                                     | ✓                            |
| Glazing options   | Internal and external beaded |
| Glazing thickness                                       | 28mm – 44mm                  |



# Visibly different

We understand the desire for slimmer sightlines, which is why the Luminia F82 has been designed with reduced outer frame rebates that are symmetrical.

Combined with a 122mm meeting style and a frame to glass sightline of 97mm the F82 boasts greater glazing areas flooding the room with more natural light than ever before.


- DESIGN FEATURES**
- 1 / Unique flush pop-out handle for ease of operation, removing the need for additional unsightly handles
  - 2 / Unique traffic door handle
  - 3 / Heavy duty compact rollers as standard
  - 4 / Both frame and cill sightlines of 97mm
  - 5 / 122mm Sillline interlock
  - 6 / Low threshold
  - 7 / Larger glazing area
- OPTIONS**
- Square bead
  - Glazing 28mm – 44mm
  - Available in a range of opening configurations
  - Available in a range of single or dual colour and anodised finishes
  - All configurations available open in and open out




Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors




## CAD Cross Sections




F82 HEAD / A




F82 MEETING STYLE / B




F82 LOCKING JAMB / C




CROSS SECTION ELEVATION



F82 WITH FACE DRAINAGE / D1



F82 CILL AND SUBCILL / D




F82 HEAD WITH 40MM  
ADDON FOR TRICKLE VENT / A1

# Beautifully organised

As with all AluK aluminium system, you'll find an extensive choice of configurations available to choose from. And as ever, all are available as open in and open out for added homeowner choice.

## TYPICAL CONFIGURATIONS



## 1 / SINGLE DOOR SIZE LIMITS (OPEN IN & OPEN OUT)

| Leaf Dimension |      |      |      | Max Weight (Kg) |
|----------------|------|------|------|-----------------|
| LB*            |      | AB*  |      |                 |
| Min            | Max  | Min  | Max  |                 |
| 550            | 1200 | 1540 | 2600 | 150             |

## 2 / DOUBLE DOOR SIZE LIMITS (OPEN IN & OPEN OUT)



| Leaf Dimension |      |      |      | Max Weight (Kg) |
|----------------|------|------|------|-----------------|
| LB*            |      | AB*  |      |                 |
| Min            | Max  | Min  | Max  |                 |
| 550            | 1200 | 1540 | 2500 |                 |

## 3 / DOOR SIZE LIMITS - NO TRAFFIC DOOR (OPEN IN & OPEN OUT)

| Leaf Dimension |      |      |      | Max Weight (Kg) |
|----------------|------|------|------|-----------------|
| LB*            |      | AB*  |      |                 |
| Min            | Max  | Min  | Max  |                 |
| 700            | 1200 | 1000 | 2600 | 150             |


## 4 / DOOR SIZE LIMITS (OPEN IN & OPEN OUT)

| Leaf Dimension |      |      |      | Max Weight (Kg) |
|----------------|------|------|------|-----------------|
| LB*            |      | AB*  |      |                 |
| Min            | Max  | Min  | Max  |                 |
| 550            | 1200 | 1540 | 2500 | 150             |



Innovators in  
Curtain Walling, Façades, Cladding, Windows & Doors





## Colourful choices

If there's one thing architects, specifiers and homeowners all have in common, it's the desire for choice. That's why we offer an extensive range of colours and finishes to bring any project vibrantly alive.

It offers customers the freedom to let their imagination fly while providing installers with the quick turnaround and clear delivery schedules they demand.

So whether it's a standard single or dual colour, or one of the many vibrant RAL Colours available, the tone is set for service excellence.

### STANDARD COLOURS

|                          |                        |
|--------------------------|------------------------|
| Hipco White<br>9910HG    | Anthraco Grey<br>7016M |
| Chocolate Brown<br>8017M | Deep Black<br>9005M    |

### STANDARD DUAL COLOURS

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| External<br>Anthraco Grey<br>7016M  | External<br>Deep Black<br>9005M     |
| Internal<br>Hipco WhiteHG<br>9910HG | Internal<br>Hipco WhiteHG<br>9910HG |

### POPULAR RAL COLOURS


|       |       |       |       |
|-------|-------|-------|-------|
| 1013M | 1015M | 7044M | 9001M |
| 7034M | 1019M | 6021M | 7032M |
| 3005M | 9010M | 6003M | 7021M |

### CUSTOM RAL COLOURS AVAILABLE



## Finishing touches

The Luminia F82 bi-fold hardware is available in a range of colours and includes a unique traffic door handle, flush pop-out T-handle; as well as improved heavy duty rollers and gearing that doesn't compromise on safety and security.





T: +44 (0) 116 2289 3343 E: [info@facadecreations.co.uk](mailto:info@facadecreations.co.uk) W: [www.facadecreations.co.uk](http://www.facadecreations.co.uk)

Registered in England, Company Number: 16267073