



Optio Inline Sliding Door

Brochure

Optio Inline Sliding Door



A premium sliding door with slim sightlines, available in a variety of sliding configurations using single, dual and triple track systems. The BSC94 offers high levels of performance, from thermal U-Values of 1.6W/m2K (double glazed), and with panel weights up to 400Kg. Smooth operation is guaranteed through the use of the highest quality fittings.




DESIGN FEATURES

- > Accepts 20 31 mm double glazing
- Max 400kg panel weight
- Certified PAS 24
- Anti bi-metal polyamide strip to allow for varying expansion rates

OPTIONS

- Available as Lift & Slide
- Slimmer sightline of 45mm available
- Multiple sliding configurations
- Mono, Dual or Tri rail options
- Available in single and dual colour; anodised finishes also available
- Range of hardware and security features

CONFIGURATIONS



SPECIFICATIONS

Performance and accreditation	BSC94	BSC94SLIM
U-value (double Glazing)* (Ug = 1.0W/m²K) (Dual Rail)	1.6 W/m²K	1.6 W/m²K
Green guide rating	C rated	C rated
Acoustic performance (dB)	Rw (C;Ctr) 36 (-1;-3) dB**	npd
Air tightness (Pa)***	Class 4 (600 Pa)	Class 4 (600 Pa)
Water tightness (Pa)***	Class 7a (300 Pa)	Class 7a (300 Pa)
Wind load (Pa)***	C4 (1600 Pa)	C4 (1600 Pa)
Security – PAS24	~	×

Configuration & frame

Opening	Inline sliding	Inline sliding
Mono rail (105mm)	~	×
Dual rail (94mm)	✓	~
Tri rail (155mm)	~	~

Size limits

Max vent weight****	400kg	400kg
Max frame height ⁺	3000mm	3000mm
Max frame height with security features	2600mm	×


System features

Dual colour option	~	✓
Multi-point locking	~	✓
Glazing options	Internal	Internal
Glazing thickness	20mm-31mm	20mm-31mm
Sightlines	85mm	45mm

CAD CROSS SECTIONS








Mono Rail – Interlock

Mono Rail – Cill

Dual Rail/Tri Rail – Standard Interlock







Dual Rail – Cill

Tri Rail – Cill

Dual Rail/Tri Rail – Standard Slimline Interlock



Innovators in

Curtain Walling, Façades, Cladding, Windows & Doors



