

Email Orders/Quotes to commercial.ops@polyframe.co.uk Please tick for quote only Page: _____ of: _____

Company Name (Acc No): _____ Please email/fax confirmation to: _____

Contact Name: _____ Order Ref/No: _____

Contact Numbers: _____ Preferred Delivery Date: _____

Please Circle Items Required

System:	Chamfered 70C / Sculptured 70S		Bead Type:	Ovolo / Flat		U value Ud:	U value required.....	
Outerframe:	Standard Large 72mm		Glass Supply:	DGU unglazed / TGU unglazed / Glazed / Loose glass		Unit Thickness:	28mm DGU / 36mm TGU / 44mm TGU	
Reinforcing:	Fully Reinforced as standard		Lock Type:	Roller lock / Yale Hook lock / Hook lock + shootbolts		Cylinder:	6 Pin / 1* Cylinder & Guard / 3* Cylinder / 6 Pin Thumbturn / 1* Thumbturn / 3* Thumbturn Cylinder	
Opening:	In / Out		Restrictors:	Y / N		Hinge Guards:	Y / N	
Colours:	External Colour:	Choices:	External Colour:	Choices:	PAS24 Upgrade*:	PPP (meets PAS24 standard)		
	White	70C, 70S	Pearl Grey**	70C	Handle Type:	Lever-Lever / Lever-Pad* / Blanking plate <small>*not available on french doors</small>		
	Golden Oak*	70C, 70S	Chartwell Green*	70C&70S	Panic Bar option:	Y / N Stable Door option: Y / N		
	Rosewood*	70C, 70S	Slate Grey Smooth*	70C	Handle Colour:	White / Black / Gold / Chrome / Satin Silver / Anthracite		
	Anthracite Grey	70C	White Woodgrain***	70S	Hinge Colour:	White / Black / Gold / Chrome / Satin Silver		
	Smooth*	70C, 70S	Clotted Cream *	70S	Trickle Vents:	None / Glazpart		
	Anthracite Grey grained*	70C	Black*	70S	TV Position:	Frame / Sash / 45mm add on		
	Irish Oak*	70C	Elephant Grey**	70C	Threshold Type:	PVCu 52mm / 62mm / 72mm / Low Ali (Exitex)		
	Key: * foils are available both sides and on white		Internal Colour:					
	** foils are available on white only		Foil both sides					
	*** foils are available both sides only		On white					
Note: Anthracite Smooth Grey both sides and on white, Irish Oak both sides and on white, Pearl Grey on white, Slate Grey Smooth both sides and on white, Pebble Grey on white and Elephant Grey on white are only available in the 70C chamfered casement suite. White grain both sides and Clotted cream both sides and on white and Black brown both sides and on white, are only available in the 70S sculptured casement suite.								

Hinge Type is Mila Pro-secure as standard.

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons	Cill	T/V area	Glass Spec (Tough, Lam, Obs, Lead)	Add-ons 15mm / 45 mm Couplers 3mm / 7.5mm / 24mm	Special Requirements (inc letterplate or cylinder colour etc)
Location:	Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000			T
	Height						B
	Transom						L
	Mullion						R
Location:	Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000			T
	Height						B
	Transom						L
	Mullion						R
Location:	Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000			T
	Height						B
	Transom						L
	Mullion						R



Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	T/V area	Glass Spec (Tough, Lam, Obs, Lead)	Add-ons 15mm / 45 mm Couplers 3mm / 7.5mm / 24mm	Special Requirements (inc letterplate or cylinder colour etc)
		Width	Height					
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	
Location:		Width		None 95 150 180 225 Concealed Face Drain	2500 4000 5000		T	
		Height					B	
		Transom					L	
		Mullion					R	

